

UNI-T®

UT15 SERIES Waterproof Type Voltage Testers UT15B / UT15C



UL 61010-1 EN 61243-3
EN 61010-1 EN 61326-1
EN 61010-2-033



■ UT15B



■ UT15C

SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT15B	UT15C
LED AC/DC Voltage Indication (V)	12V	0~12V	0~12V
	24V	17V±2V	17V±2V
	50V	35V±5V	35V±5V
	120V	80V±15V	80V±15V
	230V	165V±20V	165V±20V
	400V	300V±30V	300V±30V
Phase Rotation Test	Operating Voltage: 0V~690V	√	√
	Frequency: 50Hz~60Hz		
Single Lead(L2)Voltage Detection	Operating Voltage: 0V~690V	√	√
	Frequency: 50Hz~400Hz		
Continuity Test	Resistance: 0~100kΩ	√	√
	Beeper and LED light Indicator		
Polarity Detection	Positive & Negative	√	√
Features			
Water-Proof(IP65)		√	√
Auto Range		√	√
Work Light		√	√
Low Battery Indication	Short circuit two leads, LED and beeper off when the battery is low	√	√
LCD AC/DC Voltage Display	24V~690V		±(3%+5)

GENERAL CHARACTERISTICS

Power	1.5V Batteries(R03) × 2
LCD Size	UT15C-23 × 12mm
Product Color	Red and Grey
Product Net Weight	210 g
Product Size	275mm × 51mm × 30 mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	30 PCs
Standard Carton Measurement	440mm × 295mm × 455mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	17 Kg